




02.


- 2.1.
- 2.2.
- 2.3. VLAN-
- 2.4.

 !

'Save'


 Save


 Status


 Logout


2.1.

'Status'



 Save

 Status

 Logout

Port Status											
Port	Name	Link	Speed	State	LACP	TxPkts	RxPkts	Errors	Tx Bits/s	Rx Bits/s	Up Time
GE0/0/1		up	auto-1000M	forwarding	disabled	1419	1690	0	9760	3704	0:16:10
GE0/0/2		down	auto	disabled	disabled	0	0	0	0	0	0:00:00
GE0/0/3		down	auto	disabled	disabled	0	0	0	0	0	0:00:00
GE0/0/4		down	auto	disabled	disabled	0	0	0	0	0	0:00:00
GE0/0/5		down	auto	disabled	disabled	0	0	0	0	0	0:00:00
GE0/0/6		down	auto	disabled	disabled	0	0	0	0	0	0:00:00
GE0/0/7		down	auto	disabled	disabled	0	0	0	0	0	0:00:00
GE0/0/8		down	auto	disabled	disabled	0	0	0	0	0	0:00:00
GE0/1/1		down	1000M	disabled	disabled	0	0	0	0	0	0:00:00
GE0/1/2		down	1000M	disabled	disabled	0	0	0	0	0	0:00:00


:

☒ Any

☐ Port

Clear Counter

'Basic Setting - System Info' :

 System information settings

Product description	SNR-S2200G-8T-POE
bootrom version	V1.11
Software version	V01D01P03SP07
Product serialNo	123456789
MAC address	00:0a:6a:00:03:01
IP address	192.168.1.1 Setting
Subnet mask	255.255.255.0
Default gateway	0.0.0.0
System startup time	0-Days 1-Hours 53-Minutes 22-Seconds
System application	running default application
System name	SNR-S2200G-8T-POE Setting
System location	default location
Web page timeout (in minute)	20

:

Product description	.
Bootrom version	.
Software version	.
Product serialNo	.
MAC address	.
IP address	IP-, (192.168.1.1).
Subnet mask	, (255.255.255.0).
Default gateway	, (0.0.0.0).
System startup time	.
System application	().
System name	.
System location	.
Web page timeout (In minute)	.

2.2.

General Setup

System description

SNR-S2200G-8T-POE Switch

System object ID

1.3.6.1.4.1.40418.7.101

System port quantity

10

System startup time

0-Days 3-Hours 8-Minutes 59-Seconds

System name

SNR-S2200G-8T-POE

System location

default location

System contact

admin

Product description

SNR-S2200G-8T-POE

Refresh

Modify

'Basic Setting - General Setup'. :

- .
- .
- .

2.3. VLAN-

Vlan Interface

VlanInterfaceConf

Create:

Interface

vlan-interface

Vlan ID

1

Add

Cancel

Clear

List:

Index	Name	Primary ipaddress	VLAN	Status	Delete
1	VLAN-IF1	None	1	Up	<input type="checkbox"/>
2	VLAN-IF101	192.168.1.1	101	Up	<input type="checkbox"/>

Delete

Cancel

!

L3- VLAN. VLAN .

L3- 'Basic Setting - IP Setup'. 'Create' 'Interface' 'vlan-Interface' VLAN 'Vlan ID'. 'Add' L3-.

L3- 'Delete' 'List' VLAN.

IP- L3-, 'VlanInterfaceConf', :

Vlan Interface Config

VlanInterface

VLAN Interface Name List:

Interface Name

Vlan ID

VLAN-IF101

101

Apply

Cancel

VLAN Interface Configuration:

Mode

IP Address

IP Address

NetMask Address

0.0.0.0

0.0.0.0

Override

Add

Refresh

VLAN Interface List:

Index	Ip	Mask	Primary	Delete
1	192.168.1.1	255.255.255.0	<input checked="" type="radio"/>	<input type="checkbox"/>

Modify

Delete

Cancel

'Interface Name' VLAN, IP-. 'VLAN Interface Configuration' 'Mode' IP-:

- IP Address - IP-,
- BootP
- DHCP

'Override'.

'VlanInterface' IP- 'Gateway':

Default Gateway

VlanInterfaceConf

Gateway Configuration:

Gateway

Apply

Vlan Interface

VlanInterfaceConf

Creat:

Interface

Vlan ID

vlan-interface

1

Add

Cancel

Clear

List:

Index	Name	Primary Ipaddress	VLAN	Status	Delete
1	VLAN-IF1	192.169.1.1	1	Up	<input type="checkbox"/>

Delete

Cancel

2.4.

Port basic settings

Port Number [\[Click for selecting\]](#)

1	3	5	7	9
0	-	-	-	-
-	-	-	-	-
2	4	6	8	10

Port Number

Port basic settings Ethernet 1000M Port[1]

Port	Status	Link	Priority	Set speed	Mode	Actual speed	Port description (0-128 chars)
GE0/0/1	<div>enable</div>	up	<div>0</div>	<div>auto</div>	<div>auto</div>	full-1000M	

Refresh

Modify

Ethernet 1000M Port

GE0/0/1	enable	up	0	auto	auto	full-1000M	
GE0/0/2	enable	down	0	auto	auto	unknown	
GE0/0/3	enable	down	0	auto	auto	unknown	
GE0/0/4	enable	down	0	auto	auto	unknown	
GE0/0/5	enable	down	0	auto	auto	unknown	
GE0/0/6	enable	down	0	auto	auto	unknown	
GE0/0/7	enable	down	0	auto	auto	unknown	
GE0/0/8	enable	down	0	auto	auto	unknown	
GE0/1/1	enable	down	0	full-1000M	auto	unknown	
GE0/1/2	enable	down	0	full-1000M	auto	unknown	

'Basic Setting - Port Setup'. . . :

- / (Status);
- 802.1p (Priority);
- (Set Speed);
- (Port description).