

02- VoIP-Trunk-

VoIP Trunk- web- Basic - Trunks - New VoIP Trunk.

- VoIP-Trunk-

VoIP-Trunk-

VoIP Trunk web- Basic - Trunks - New VoIP Trunk

Edit SIP trunk trunk-sip-800

X

Description: test_152

Peer Mode: ☐

Host: 172.20.0.2 :5060

Maximum Channels*: 0

Prefix:

Outbound CID:

☐ Without Authentication

Username: 152

Authuser: 152

Password: ●●●●●●

☒ Advanced Options

Fromdomain: 172.20.0.2

Insecure: port,invite

Fromuser: 152 x

Qualify(sec): ☒ 2

DID Number:

Transport: UDP ▾

DTMF Mode: RFC2833 ▾

NAT: ☐

SRTP: ☐

Auto Fax Detection: ☐

Context: Default ▾

Language: Default ▾

Audio Codecs

☒ ulaw ☒ alaw ☐ G.722 ☐ G.729 ☐ G.726 ☐ GSM ☐ Speex

Video Codes

☐ H.261 ☐ H.263 ☐ H.263+ ☐ H.264

Save

Cancel

- Description , , , test_152
- Protocol — VoIP SIP,
- Host:port — SIP . Host:port SIP - 172.20.0.2 5060 (,)
- Without Authentication — , , ,
 - Username - 152, SIP
 - Authname - 152, SIP
 - Password , SIP
- Advanced Options

- From Domain SIP - 172.20.0.2
- From User , SIP

- Audio Codecs , SIP - *ulaw alaw*.

«Save» «Activate Changes».



, Operator SIP-trunk (SIP .)

Enterprise IP-PBX LVX-Series

Logout

• Home

• Operator

Basic

Inbound Control

Advanced

Network Settings

Security

Report

System

Operator

Idle

Ringing

InUse

Hold

UnAvailable

800

800(SIP)

805

805(SIP)

801

801(SIP)

806

806(SIP)

802

802(SIP)

807

807(SIP)

803

803(SIP)

808

808(SIP)

804

804(SIP)

809

809(SIP)

Total: 10

Online: 1

Current Call(s): 0

Status

Trunk Name

Type

Username

Hostname/IP/Port

Reachability

Registered

test_152

SIP

152

172.20.0.2:5060

OK (1 ms)

Registered

serg_erlang

SIP

2209030

sw.erlang.ru:5060

OK (1 ms)